

DOUGLAS FIR POLE SIZING CHART												
Class	H-6	H-5	H-4	H-3	H-2	H-1	1	2	3	4	5	6
Minimum Circumference at Top (Inches)	39	37	35	33	31	29	27	25	23	21	19	17
Length of Pole (Feet)	Minimum Circumference at 6 feet from Butt (Inches)											
20	-	-	-	-	-	-	31.0	29.0	27.0	25.0	23.0	21.0
25	-	-	-	-	-	-	33.5	31.5	29.5	27.5	25.5	23.0
30	-	-	-	-	-	-	36.5	34.0	32.0	29.5	27.5	25.0
35	-	-	-	-	43.5	41.5	39.0	36.5	34.0	31.5	29.0	27.0
40	-	-	51.0	48.5	46.0	43.5	41.0	38.5	36.0	33.5	31.0	28.5
45	58.5	56.0	53.5	51.0	48.5	45.5	43.0	40.5	37.5	35.0	32.5	30.0
50	61.0	58.5	55.5	53.0	50.5	47.5	45.0	42.0	39.0	36.5	34.0	-
55	63.5	60.5	58.0	55.0	52.0	49.5	46.5	43.5	40.5	38.0	-	-
60	65.5	62.5	59.5	57.0	54.0	51.0	48.0	45.0	42.0	39.0	-	-
65	67.5	64.5	61.5	58.5	55.5	52.5	49.5	46.5	43.5	40.5	-	-
70	69.0	66.5	63.5	60.5	57.0	54.0	51.0	48.0	45.0	41.5	-	-
75	71.0	68.0	65.0	62.0	59.0	55.5	52.5	49.0	46.0	-	-	-
80	72.5	69.5	66.5	63.5	60.0	57.0	54.0	50.5	47.0	-	-	-
85	74.5	71.5	68.0	65.0	61.5	58.5	55.0	51.5	48.0	-	-	-
90	76.0	73.0	69.5	66.5	63.0	59.5	56.0	53.0	49.0	-	-	-
95	77.5	74.5	71.0	67.5	64.5	61.0	57.0	54.0	-	-	-	-
100	79.0	76.0	72.5	69.0	65.5	62.0	58.5	55.0	-	-	-	-
105	80.5	77.0	74.0	70.5	67.0	63.0	59.5	56.0	-	-	-	-
110	82.0	78.5	75.0	71.5	68.0	64.5	60.5	57.0	-	-	-	-
115	83.5	80.0	76.5	72.5	69.0	65.5	61.5	58.0	-	-	-	-
120	85.0	81.0	77.5	74.0	70.0	66.5	62.5	59.0	-	-	-	-
125*	86.0	82.5	78.5	75.0	71.0	67.5	63.5	59.5	-	-	-	-
	H-6	H-5	H-4	H-3	H-2	H-1	1	2	3	4	5	6

* 125' Availability: Untreated Only