

**ESTIMATED HANDLING WEIGHTS FOR DOUGLAS FIR FULL LENGTH TREATED POLES**

*Very Dry Climate/Material Could Run as much as 15% lighter*

Class	H-6	H-5	H-4	H-3	H-2	H-1	1	2	3	4	5	6
<b>Length of Pole (Feet)</b>	<b>Estimated Weight (lbs)</b>											
20	-	-	-	-	-	-	620	564	489	395	329	287
25	-	-	-	-	-	-	846	743	672	522	465	385
30	-	-	-	-	-	-	1109	973	888	658	588	494
35	-	-	-	-	-	-	1349	1184	1086	855	729	611
40	-	-	-	-	-	-	1669	1476	1297	1025	879	743
45	-	-	-	-	-	-	2026	1800	1593	1269	1039	-
50	4305	3915	3746	3417	2938	2519	2336	2087	1622	1481	-	-
55	5161	4771	4263	3915	3440	2933	2665	2383	1866	1706	-	-
60	6002	5461	4916	4489	4023	3530	3013	2703	2124	1861	-	-
65	6745	6143	5541	5029	4512	3990	3384	3036	2397	2101	-	-
70	7567	6909	6242	5645	5029	4479	3647	3393	2693	-	-	-
75	8390	7741	6900	6190	5532	4902	4183	3633	3003	-	-	-
80	9203	8479	7623	6810	6101	5414	4615	4019	3337	-	-	-
85	10110	9268	8343	7464	6698	5955	5236	4583	3685	-	-	-
90	11158	10279	9198	8310	7323	6519	5546	5020	4051	-	-	-
95	12088	11125	10002	8925	7967	7121	5668	5302	-	-	-	-
100	13047	11999	10838	9616	8606	7689	6561	5767	-	-	-	-
105	14053	12925	11628	10458	9320	8343	6890	6260	-	-	-	-
110	15096	14133	12704	11426	10105	8982	7445	6561	-	-	-	-
115	16182	14833	13306	12084	10838	9616	8028	7088	-	-	-	-
120	17197	15773	14265	12873	11487	10274	9005	7981	-	-	-	-
	<b>H-6</b>	<b>H-5</b>	<b>H-4</b>	<b>H-3</b>	<b>H-2</b>	<b>H-1</b>	<b>1</b>	<b>2</b>	<b>3</b>	<b>4</b>	<b>5</b>	<b>6</b>